

## Sewing Pattern — Dress 2023

Recommendations on fabric: thin well draping fabrics suitable for dresses of natural or mixed fibers (crepe-chiffon).

You will also need: lining; fusing; blind zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 1 cm, hem of the skirt - 2 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Central back part - 2 details
2. Side back part - 2 details
3. Side front part - 2 details
4. Central front part – 1 detail
5. Back belt - 2 details
6. Front belt - 1 detail
7. Top skirt - 1 detail
8. Under skirt - 1 detail
9. Facing - 2 details

#### Lining:

1. Central back part - 2 details
2. Side back part - 2 details
3. Side front part - 2 details
4. Central front part – 1 detail
5. Back belt - 2 details
6. Front belt - 1 detail

#### Fusing:

1. Back belt - 2 details
2. Front belt - 1 detail
3. Facing – 1 detail

## **INSTRUCTIONS:**

1. Apply fusing to details of the back part belt, front part belt and facings.
2. Fold facings right sides together and overstitch neckline edge. Press seam allowances, slash on rounded parts. Turn the facing onto right side, serge, press.
3. Sew relief edges of front and back parts, press seam allowances towards center, serge.
4. Stitch back part belt to top part, press seam onto belt, serge. Stitch front part belt to top part, press seam onto belt, serge.
5. Sew side seams, press seam onto back part, serge.
6. Overstitch details of lining the same way. Fold lining with main fabric right sides together and overstitch edges of the armhole, press seam allowances, slash on rounded parts. Turn waist onto right side and then trim as one detail. Serge middle edge of back part.
7. Stitch outer facing to top edge of front part, slash seam allowances and press on the facing. Stitch outer facing to top edge of back part, slash seam allowances and press on the facing. Press untrimmed edge of outer facings onto wrong side.
8. Serge middle edges of top and under skirts. Put top skirt on under and fix on top and middle edges up to marker. Stitch skirt to the dress, press seam allowances on belt and serge.
9. Sew middle edge of back part from marking downwards separately on every skirt. Press seam apart, pressing seam allowance for closure. Lay zipper under seam allowances so that zipper blades will not be seen and stitch. Press seam allowance of inner facing onto wrong side and topstitch in facing connecting seam. Turn short edges and fix to zipper.
10. Press top and under skirts hem seam allowance onto wrong side, turn inside and topstitch.

## **TECHNICAL DRAWING:**

