

Sewing Pattern — Dress 2022

Recommendations on fabric: well-draping knit fabric

You will also need: elastic thread

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance on hem – 1.5 cm, all other seams 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Back – cut 1
2. Upper front – cut 2
3. Lower front – cut 1 on fold

INSTRUCTIONS:

1. Sew shoulder seams, serge, and press toward back.
2. Serge edge of neckline. Turn seam allowance onto wrong side, press, and topstitch.
3. Serge top straight edge (the part 4-5 cm wide) of lower front and similar edge of top front. Turn seam allowance onto wrong side, press and topstitch.
4. Make a gathering stitch along top curved edge of lower front and gather fullness, placing gathers closer to center. The length of gather is mentioned on the paper pattern.
5. Pin together curved edges of top front with each other, right sides together, and sew

with similar edge of lower front. Serge and press. Thread right detail into resulting slit and sew correspondingly.

6. Turn lower edge of top front under at notch near side seam and baste top and bottom front together along side edge.

7. Sew center back seam. Serge and press toward left.

8. Sew side seams. Serge and press toward back.

9. Serge lower edge of garment and edge of the armhole. Turn onto wrong side, press, and topstitch.

TECHNICAL DRAWING:

