

Sewing Pattern — Raglan jacket 4173

Recommendations on fabric: natural or mixed lightweight coat fabrics (cashmere)

You will also need: lining, fusible interfacing, raglan shoulder pads, 3 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem of the garment and hem of sleeve – 3 cm; all other seams – 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back - cut 1
2. Front - cut 2
3. Back sleeve – cut 2
4. Front sleeve –cut 2
5. Stand-up collar – cut 2
6. Back neck facing –cut 1
7. Front band facing – cut 2

Lining:

1. Back - cut 1
2. Front - cut 2
3. Back sleeve – cut 2
4. Front sleeve – cut 2

*ATTENTION: Back sleeve, front sleeve and front pieces are cut from lining excluding the width of back neck facing and front band facings.



Fusible interfacing:

1. Stand-up collar – cut 1
2. Front band facing – cut 2
3. Back neck facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to front band facings, back neck facing, and outer stand-up collar.
2. Sew center seam of back sleeves. Press seam apart.
3. Sew darts on front. Press toward hem.
4. Sew back sleeve to back, press seam onto the sleeve. Make a decorative stitch along the seam at 0.7 cm. Sew front sleeve to front, press seam onto the sleeve. Make a decorative stitch along the seam at 0.7 cm. Sew outer seam of sleeve. Press seam allowances toward front. Make a decorative stitch along the seam at 0.7 cm.
5. Sew shoulder seams of back neck facing and front band facings. Press seam allowances apart. Sew inner stand-up collar to neckline of facing. Clip into curves and press seam apart.
6. Sew outer stand-up collar into the neckline of the main garment. Clip into curves and press seams apart.
7. Pin facing onto right side of the garment and sew center front and stand-up collar. Trim corners, turn onto right side, and straighten.
8. Sew lining the same way as main fabric pieces, leaving an opening in lower seam of right sleeve for turning. Sew lining to inner facing edges. Fix allowances of stand-up collar connecting seams close to seams. Sew lower edge of front band facing along hemline, trim corners. Mark and press hem of the garment onto wrong side. Sew hem of the garment and hem of sleeve with lining. Turn garment through the opening in sleeve and sew up the opening. Make a decorative stitch along center front, hem of the garment, collar, and hem of sleeves at 0.7 cm from the edge.
9. Make buttonholes on right front, sew buttons on left front.

TECHNICAL DRAWING:

