

Sewing Pattern — Skirt 2014

Recommendations on fabric: stiff satin

You will also need: zipper of 20 cm length; fusing; lining; stiff organza.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 2 cm for back middle seam (to stitch the zipper) and skirt hem. 1 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Satin:

1. All skirt pieces as well as facings

Fusing:

1. All facings.

Lining:

1. All lining pieces

Stiff organza:

1. All skirt pieces

INSTRUCTIONS:

concerning work with skirt hem (clear edge, organza):

1. The zipper is in middle back seam.
2. Process the hem at clear edge with stiff organza (see photo). First, cut organza piece's lower edge to make the detail 1 cm shorter than satin skirt. Stitch satin skirt to organza skirt along lower edge, then turn them right side out. Do the same for all skirt hems separately.

3. Overseam all skirt vertical seams (organza and satin as one layer). Then stitch all skirts together, press seams apart (see photo). Fold hem seam corners inside and fix them with blind stitches.

4. Apply the fusing to facing. Stitch facings on skirt lining, then stitch skirt upper edge around.

TECHNICAL DRAWING:

