

Sewing Pattern — Skirt 2012

Recommendations on fabric: medium to heavy-weight satin

You will also need: zipper of 20 cm length; fusible interfacing, lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 2 cm for back middle seam (to stitch the zipper) and skirt hem. 1 cm for other seams.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

Front- cut 1
Center back- cut 2
Side back- cut 2
Train- cut 1
Front facing - cut 1
Back facing - cut 2

Lining:

Front- cut 1
Center back -cut 2
Side back- cut 2

Fusible interfacing: facings

INSTRUCTIONS:

1. Apply interfacing to facings.
2. Sew side backs to center backs, matching notches. Serge and press seams toward center.
3. Sew train to one side of center back, matching notches. Then sew the opposite center back seam from zipper-end mark down and then along opposite side of train. Serge and press seams toward center.
4. Insert invisible zipper.
5. Sew side seams. Serge and press seams toward back.
6. Sew lining together in the same manner as main fabric pieces (there is no train in lining).
7. Pin lining to inside of skirt, baste along waist. Slipstitch opening for zipper in center back along zipper tape.
8. Sew side seams of front and back facing. Press seams open. Serge facing outer edge.
9. Pin facing to skirt, right sides together, and sew. Understitch, turn under, and press. Slipstitch facing ends to zipper tape and tack at seams. Attach hook and eye, if desired.

TECHNICAL DRAWING: