

## Sewing Pattern — Jacket 4171

Recommendations on fabric: coat fabrics of natural or mixed fibers.

You will also need: fusing; 3 buttons; lining; shoulder pads; sleeve heads

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams – 1 cm, on hem of the garment and of sleeve 4 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### CUTTING:

#### Fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central front part – 2 details
5. Buttonstand – 2 details
6. Stand-up part of collar – 2 details
7. Upper sleeve part – 2 details
8. Lower sleeve part – 2 details
9. Back neckline facing – 1 detail
10. Flap – 4 details
11. Pocket facing – 4 details
12. Lower part decoration – 1 detail
13. Flower – 1 detail

#### Lining:

1. Side back part – 2 details
2. Side front part – 2 details
3. Upper sleeve part – 2 details
4. Lower sleeve part – 2 details
5. Central back part – 2 details
6. Central front part – 2 details
7. Pocket bag – 4 details

**ATTENTION:** Front part and back part lining details are cut as main details except for the buttonstands width and back part neckline facings accordingly.

**Fusing:** Buttonstand, back part neckline facing, stand-up part of collar, central front part, flap, pocket facing.

## **INSTRUCTIONS:**

1. Apply fusing to buttonstand, back neckline facing, stand-up part of collar, central front part, top flaps, facings of pocket, edge of the armhole on front part and on back part. Apply fusing to pockets location on central and side front parts.
2. Mark darts on front part and on back part. Sew and press darts onto back part towards center. Sew darts on front part, slash depth of darts away and press apart.
3. Sew relieve seams on back part and on front part, press seam allowances apart. Sew and press apart middle edge of back part.
4. Fold flaps details right sides together and overstitch. Slash seam allowances in corners of flaps, slash on rounded parts, turn onto right side.
5. Mark pocket location. Fold facings of pocket in half wrong sides together and press. Mark additional line on facing of pocket parallel to facing fold to connect it. Mark additional line on flap for connection parallel to flap top edge, measuring flap width on the whole length. Mark additional lines parallel to pocket opening for flap and facings connection. Stitch lining of pocket to flap. Stitch facings to front part. Finish stitches near parallel lines of pocket marking. Check you stitched facings from wrong side correctly (stitches must be parallel). Cut the pocket opening. Make cross slashes at 1-1, 5 cm off pocket's end. Turn facings onto wrong side through given slit, straighten edges, straighten ends of the facings so that pressed folds of the facings come edge-to-edge. Fix ends of pocket from wrong side with double back stitch on corners base. Insert flap into pocket and stitch to top facing of pocket. Stitch lower lining of pocket into connecting seam of lower facing, cut and sew lining of pocket.
6. Sew and press apart shoulder and side edges.
7. Fold top stand-up part of collar with lower and overstitch. Start and finish the stitch exactly near marked line of stand-up part of collar connecting seam. Slash seam allowances in corners. Turn stand-up part of collar out, straighten and press.
8. Sew and press apart shoulder edges of back part neckline facing and buttonstands.
9. Put buttonstand onto right side of front part right side downwards, pin together and overstitch buttonstand, lapel, gorge seam and lower buttonstand corner. Slash seam allowances in corners. Topstitch seam allowance of buttonstand: on closure section – onto buttonstand. Stitch at 0, 2 cm off the seam. Turn stands onto right side, straighten seams. Press hem of the garment.
10. Sew outer stand-up part of collar into the neckline of jacket, and inner stand-up part of collar into the back part neckline facing and buttonstands. Press allowances of connection seams apart.
11. Sew and press apart elbow edge of sleeve. Press hem of sleeve. Sew and press apart front edge of sleeve.
12. Sew sleeves into armholes according to notches. Sew in shoulder pads and sleeve heads.
13. Sew seams on lining details and sew in sleeves, leaving a slit in front right seam of sleeve.
14. Stitch lining to inner buttonstand edges and back part neckline facing. Fix allowances of stand-up part of collar connection seams close to seams.
15. Stitch lining to hem of jacket sleeve. Turn jacket out through the slit in sleeve. Sew slit in sleeve.
16. Put decorative stitch along buttonstand, stand-up part of collar, hem of jacket and hem of sleeve.
17. Serge buttonholes on right front part. Sew buttons on left front part accordingly.
18. Fold lower part of decoration in half lengthwise right sides together and overstitch on three sides, leaving a slit for turning out. Turn detail onto right side, sew a slit. Stitch crosswise loosely

and gather slightly. Topstitch decoration on shoulder section according to technical drawing.  
19. Fold flower detail in half lengthwise right sides together and overstitch on three sides, leaving a slit for turning out. Turn detail onto right side, sew a slit. Stitch along long edge loosely and gather ruffles. Shape a flower from the detail and fasten it on lower part of decoration.

**TECHNICAL DRAWING:**

