

## Sewing Pattern — Stole 2002

Recommendations on fabric: sheer fatin

You will also need: lace border of 2 cm width

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams (excluding flounce patterns)

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fatin:

1. Stole with one-piece sleeves
2. Wide/narrow flounces of square

Lace border: sew to ready stole, then bead.

### **INSTRUCTIONS:**

1. Cut wide/narrow flounces of square shape along “cutting” line. Lay narrow flounce on the wide one, stitch them together catching stole’s edges (stitch flounces’ inner diameter to stole, with free ends – see picture). Stitch flounces to stole’s long edges only.
2. Hide stitching edges with lace border (you need approximately 6 m of lace border).
3. Stitch flounces to sleeve edges also, then overlap with lace borders. Stitch sleeves up to marks with inner seam.

**TECHNICAL DRAWING:**

