

Sewing Pattern — Sweatshirt 6131

Recommendations on fabric: medium stretch French terry or fleece

You will also need: separating zipper, bias tape of the same color as main fabric

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Center right front– cut 1
2. Center left front – cut 1
3. Side front – cut 2
4. Back – cut 2
5. Sleeve –cut 2
6. Collar – cut 2
7. Lower band (placket) – cut 1
8. Cuff – cut 2
9. Pocket lining – cut 2

INSTRUCTIONS:

1. Cut bias tape that is as long as pocket opening (use main fabric). Fold in half lengthwise and press. Unfold and press long edges toward center. Fold in half lengthwise and press. Sew pocket opening with bias tape. Serge rounded edge of pocket lining. Pin side front onto lining and topstitch along rounded line. Fix lining and side front along the lower edge with a 0.5 cm stitch from the hem.
2. Sew center back seam. Serge and press toward left. Topstitch at 0.5 cm from the seam.
3. Sew left and right fronts to side fronts. Serge, press seams toward side and sew a decorative stitch or topstitch at 0.5 cm from the seam.
4. Sew side seams. Serge and press seams toward back.
5. Serge outer edge of center right front. Turn seam allowance under and topstitch.
6. Stitch upper edge of lower band to lower edge of sweatshirt, slightly stretching the band. Serge lower edge of band. Pin right side of zipper onto right princess edge, starting from the center of lower band and finishing near zipper notch with teeth facing toward side seam. Turn zipper out along with lower part of band, press center right side onto zipper and sew. Serge and press to side edge. Sew a decorative stitch at 0.5 cm from the seam. Put left part of zipper onto outer edge of left front, starting from the center of lower band and finishing near zipper notch with teeth facing toward side seam. Turn zipper with lower part of band and stitch. Serge and press to side edge. Sew a decorative stitch at 0.5 cm from the seam. Turn inner edge of band upwards and stitch into connecting seam of outer part of band.
7. Sew shoulder seams. Serge, and press toward back. Topstitch at 0.5 from the edge.
8. Pin collars right sides together and sew along outer edge. Clip into curves and turn collar right side out and press. Sew a decorative stitch on outer edge at 0.5 cm from the edge. Fold bias tape in half lengthwise, wrong sides together, and press. Pin collar to sweatshirt, right sides together, and baste in place. Cover seam allowance by sewing bias tape along basted seam of hood and garment. Trim seam. Fold bias tape over seam, and topstitch onto sweatshirt. Turn the ends of bias tape under.
9. Sew sleeve seam. Serge seam and press seam toward back. Fold cuff right sides together and sew into ring. Fold cuff in half lengthwise and stitch to the sleeve. Serge seam allowance. Sew in sleeve, matching notches. Serge seam and press toward garment. Sew a decorative stitch at 0.5 cm from the seam.

TECHNICAL DRAWING:

