

Sewing Pattern — Jacket 6115

Recommendations on fabric: whipcord;

You will also need: lining (also mesh knitted fabric, fleece for warmer variant); warmer; fusing; 1 separable zipper (length depends on front garment length including stand-up collar height); 2 zippers (length depends on pocket's length); elastic braid of 5.5 cm width for waistcoat; elastic braid of 4.5 cm width for cuffs.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

(On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Right front part – 1 piece
2. Left front part – 1 piece
3. Back part – 1 piece
4. Back yoke – 1 piece
5. Right front yoke – 1 piece
6. Left front yoke – 1 piece
7. Right side part – 2 pieces
8. Left side part – 2 pieces
9. Center sleeve – 2 pieces
10. Lower right sleeve – 2 pieces
11. Lower left sleeve – 2 pieces
12. right sleeve insert – 2 pieces
13. Collar – 2 pieces
14. Cuff – 2 pieces
15. Front band – 2 pieces
16. Waistband – 1 piece
17. Waistband placket – 2 pieces



18. Large sacking – 2 pieces
19. Small sacking – 2 pieces
20. Off-set welt – 2 pieces

Lining:

21. Front part – 2 pieces
22. Back part – 1 piece
23. Sleeve – 2 pieces

Warmer:

Topstitch the warmer to wrong side of collar (1 detail) and waistband placket according to contour.

INSTRUCTIONS:

1. Apply the fusing to wrong side of the welt, press the welt along the center. Lay fusing reinforcement under pocket place. Mark a line on the welt determining ready welt's width. Lay the welt on right side of front part coinciding pocket marking and the line on the welt. Welt's outer side must coincide with front part's right side. Stitch the welt. Cut pocket entrance between marking lines making diagonal slashes towards corners of pocket marking. Turn the welt wrong side out. Press seam allowances apart. Lay the zipper under pocket entrance. Stitch the zipper on right side of front part at 0.1 cm from pocket entrance. Stitch small sacking to zipper's lower braid, then fold it under. Stitch large sacking to zipper's upper braid. Stitch sackings' edges together. Sacking edges must enter the seam joining the zipper and reach the hem.
2. Stitch pieces of right front part and left front part discretely, in the same way as back pieces. Topstitch joining seams along details of dark fabric. Stitch shoulder edges. Topstitch shoulder seam at back part. Stitch left/right sleeves discretely. Topstitch joining seams along details of dark fabric. Stitch sleeves into open armholes. Topstitch joining seams along armholes. Stitch side seams and sleeve seams. Stitch outer collar into neckline.
3. Press front band's inner edge under and topstitch front band on front part lining. Stitch lining details excepting a segment into a sleeve (to turn the garment right side out). Stitch inner collar into lining neckline.
4. Stitch cuffs and elastic braid into rings separately. Insert elastic braid into cuffs, stretch it to cuff's length and make 2 decorative stitches.
For manufacture stitching, first fix elastic braid into cuffs, and then stitch them into a ring. Stitch cuffs to sleeve catching elastic braid's edge into the seam.
5. Fix elastic braid into waistband making 2 decorative stitches. Stitch waistband plackets to waistband. Stitch the waistband to the jacket. Fix plackets on wrong side on front part lining.
6. Lay zipper's part on edging right sides together (teeth are outwards edging). Overstitch edgings and collar edges with lining inserting the zipper. Overstitch the collar and stitch it into the neckline. Turn the garment right side out.
7. Stitch the lining to cuffs and waistband. Sew technological hole in the sleeve.
8. Topstitch edgings and collar.

9. Press ready jacket.

TECHNICAL DRAWING:

