

Sewing Pattern — Trousers 6111

Recommendations on fabric: whipcord.

You will also need: lining; fusing; elastic braid of 4.5 cm width for waistband; elastic cord for trousers hem; 4 metal clocks; cord for waistband; Velcro.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams, 4.5 cm for hems, 0 cm for lining hem (lining reaches hem line).

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Waistband – 1 piece
4. Sacking – 2 pieces
5. Side part – 2 pieces
6. Side flap – 2 pieces
7. Side pocket – 1 piece

Lining:

8. Front part – 2 pieces
9. Back part – 2 pieces

INSTRUCTIONS:

1. Reinforce pocket entrance at front part. Stitch sacking to front part and turn into wrong side. Topstitch pocket entrance. Lay front part on side one along coincidence line and stitch sackings.
2. Stitch side seams, then topstitch. Stitch middle seams. Topstitch along left part.

3. Reinforce the pocket. Overstitch the pocket, turn right side out and topstitch. Press pocket's upper allowance under and topstitch it. Press side pocket's allowances under. Topstitch Velcro. Topstitch the pocket with flap on right side according to marks.

4. Mark lines of topstitching the elastic braid at waistband. Pierce 2 holes (at 8 cm distance) for cord between topstitchings at front part's middle seam level. Stitch separately waistband and elastic braid in ring. Insert elastic braid into waistband, stretch the braid to waistband's length and make 2 decorative stitches. Stitch the waistband to trousers catching elastic braid.

5. Stitch lining's side seams and middle seam. Stitch the lining to garment's waistband.

6. Set blocks into hems. Press hems first at 1 cm, then 3.5 cm under.

7. Stitch fabric/lining inside leg seams.

8. Topstitch hems.

9. Press ready trousers.

10. Pull cords into waistband and hems.

TECHNICAL DRAWING:

