

Sewing Pattern — T-shirt 6108

Recommendations on fabric: medium stretch-knit

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: 0.8 cm for all seams, 2 cm for garment/sleeve hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Upper front – cut 1
2. Lower front – cut 1
3. Large front insert– cut 1
4. Small front insert – cut 1
5. Back– cut 1
6. Sleeve – cut 2
7. Neckband (collar) – cut 1



INSTRUCTIONS:

1. Sew large inset to upper front, small inset to large inset and lower front to small inset (refer to sketch). Sew shoulder seams, serge and press toward back. Sew sleeves into open armholes. Serge and press seam toward garment. Topstitch at .5 cm from seam. Sew side seams and sleeve seams with one stitch. Serge seams and press toward back.
2. Sew short sides of neckband into a ring, right sides together, then fold in half. Sew the neckband to the neckline stretching it equally along neck edge. Place the neckband seam close to front center segment. Topstitch neckband joining seam with stretchable stitch, or coverstitch.
3. Serge lower edge of garment and lower edge of sleeves. Turn hem allowance onto wrong side and topstitch with stretchable stitch or coverstitch. Press.

TECHNICAL DRAWING:

