

Sewing Pattern — Trousers 6100

Recommendations on fabric: jersey or fleece;

You will also need: fusing; 4.5 cm width elastic braid for waistband; cord for waistband; Velcro.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 3 cm for garment hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Front part – 2 pieces
2. Side part – 2 pieces
3. Back part – 2 pieces
4. Waistband – 1 piece
5. Front pocket – 2 pieces
6. Back pocket – 1 piece

ADVICE: to prevent seam from stiffing, sew details with special (zig zag) stitch. To prevent hem from stiffing neaten it with overlock and then stitch using double needle. Do the same for all edges which must stay elastic.

The above is not for industrial manufacturing.

INSTRUCTIONS:

1. Press front pocket's upper edges under and topstitch it. Lay the pocket on side part along marking of pocket's lower edge, right sides together (pocket's upper edges towards trouser hems). Topstitch the pocket along lower edge. Fold the pocket upwards and press it.
2. Press back pocket's upper edge under and topstitch it. Press back pocket's allowances under. Topstitch Velcro. Topstitch the pocket in according to marking.
3. Stitch front seams catching pocket's edges. Topstitch front seams. Stitch side seams, then

topstitch. Stitch middle seams, then topstitch along left part.

4. Mark lines of topstitching the elastic braid at waistband. Pierce 2 holes (at 8 cm distance) for cord between topstitchings at front part's middle seam level. Stitch separately waistband and elastic braid in ring. Insert elastic braid into waistband, stretch the braid to waistband's length and make 2 decorative stitches. Stitch the waistband to trousers catching elastic braid.

5. Press hems into wrong side.

6. Stitch inside leg edges.

7. Topstitch hems.

8. Press ready trousers.

9. Pull the cord into waistband.

TECHNICAL DRAWING:

