

## Sewing Pattern — Trousers 6099

Recommendations on fabric: whipcord;

You will also need: lining; fusing; 2 zippers (depending on pocket's length); elastic braid of 4.5 cm width for waistband; elastic cord for hems; 4 metal blocks; cord for waistband.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 4.5 cm for hems, 0 cm for lining hems (lining reaches hem line).

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

(On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

#### Main fabric:

1. Front part – 2 pieces
2. Back part – 2 pieces
3. Waistband – 1 piece
4. Large sacking – 2 pieces
5. Small sacking – 2 pieces
6. Off-set welt – 2 pieces

#### Lining:

7. Front part – 2 pieces
8. Back part – 2 pieces

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of off-set welt, press it along the center. Apply the fusing to pocket place. Mark a line determining ready welt's width on the welt. Topstitch the trimming on welt's outer side (welt's outer side coincides with front part's right side). Stitch the welt. Cut pocket entrance between marking lines diagonally towards pocket marking's corners. Turn the welt wrong side out. Press seam allowances apart. Lay the zipper under pocket entrance. Stitch the zipper at 0.1 cm from pocket entrance on front part's right side. Stitch small sacking to zipper's lower braid, then fold it under. Stitch large sacking to zipper's upper braid. Stitch sackings' edges. Sackings' edges must



enter into seam joining the waistband.

2. Stitch side seams, then topstitch. Stitch middle seams and topstitch along left part.

3. Mark lines of topstitching the elastic braid at waistband. Pierce 2 holes (at 8 cm distance) for cord between topstitchings at front part's middle seam level. Stitch separately waistband and elastic braid in ring. Insert elastic braid into waistband, stretch the braid to waistband's length and make 2 decorative stitches. Stitch the waistband to trousers catching elastic braid.

4. Stitch lining's side seams and middle seam. Stitch the lining to garment's waistband.

5. Set blocks into hems. Press hems first at 1 cm, then 3.5 cm under.

6. Stitch fabric/lining inside leg seams.

7. Topstitch hems' allowances.

8. Press ready trousers.

9. Pull cords into waistband and hems.

**TECHNICAL DRAWING:**

