

Sewing Pattern — Trousers 6061

Recommendations on fabric: silk of 150 cm width

You will also need: fusing; 2 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Closure facing – 2 pieces
2. Front part – 2 pieces
3. Back part – 2 pieces
4. Back facing – 1 folded piece

Fusing: back facing, closure facing

INSTRUCTIONS:

1. Apply the fusing to wrong side of back facing and closure facing.
2. Sew back darts.
3. Sew side and inside leg seams. Press the allowances apart and blank them.
4. Insert parts one into another one right sides together, then sew the middle seam.

5. Sew the facing and back part, turn it into wrong side, then topstitch.
6. Press hem allowances to the wrong side, then fold and topstitch.

TECHNICAL DRAWING:

