

Sewing Pattern — Trousers 6058

Recommendations on fabric: gabardine of 150 cm width

You will also need: lining; fusing; zipper; 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Front pocket facing – 2 pieces
3. Front underlay piece – 2 pieces
5. Back underlay piece – 2 pieces
6. Back pocket facing – 2 pieces
7. Belt loops – 5 pieces
8. Button catch – 1 piece
9. Fly front – 1 piece
10. Front part – 2 pieces
11. Back part – 2 pieces
12. Waistband left part – 1 piece
13. Waistband right part – 1 piece

Lining:

2. Front sacking – 2 pieces
4. Back sacking – 2 pieces

Fusing: waistband details, button catch, fly front

INSTRUCTIONS:

1. Apply the fusing to wrong side of waistband, button catch and fly front.
2. Sew back darts and press them toward the center. Make pleats into front parts toward the center, then tack them to upper edge.
3. Make cut pockets into back parts: press 4-cm stripe of interfacing on the back part wrong side pocket marking. Topstitch the underlay piece on the lining. Press pocket facings along the center, right side over. Pin the facing along the pocket entrance, from down (the folding from the marked line), then pin the sacking, from upper, coinciding the edge and the marking. Stitch on 1 cm from the line. Cut the back part between stitched lines, cutting stitch ends diagonally. Be careful with facing and sacking when cutting! Press the seam allowances on the garment. Turn the facings into wrong side so that create a neat frame, then tack. From the right side, make a stitch strictly on the facing joining seam. Turn small triangles at hole ends into wrong side, then topstitch strictly on the facing from one stitch ends to another stitch ends. From the wrong side, sew pocket sacking free end to facing joining seam allowances, then press sacking downward, make them equal, then stitch.
4. Make slip pockets into back part in the same way as into front ones.
5. Sew front middle seam 3-4 cm downward the closure. Stitch the button catch to garment left part, press it to wrong side, then topstitch. Press right edge allowance to wrong side and tack zipper braid, with its teeth closely to the bending. Fold the button catch along the center, with its wrong sides together, then neaten the lengthwise folding and the rounded one. Tack the ready edge, placing it under slit right side and the zipper. Topstitch the right side along the edge, joining the zipper and the button catch. Pin free middle lines together. Pin zipper ready braid to left side facing, then stitch; do not catch the front part. Then stitch the left part along the marking, catching facing and the zipper.
6. Sew inside leg seams. Neaten allowances.
7. Fold belt loops along the center, tuck and topstitch them. Sew belt loops to garment upper edge: on front part – above pleats, on back part – by sides of darts, near side seams.
8. Sew belt details to upper edge of the garment, sewing the closure allowance to button catch. Fold the belt detail along the center, then stitch front short edges. Sew the slit in front middle seam, then, with the same stitch, the back middle seam up to the waist upper edge. Turn waistband inner edges under and topstitch along joining seams. Turn belt loops upward and sew them to waistband upper edge. Turn the fifth belt loop under and sew it on back middle seam.
9. Turn hem allowances under, then sew with blind stitches.
10. Make a buttonhole into waistband left end, sew the button on right one.

TECHNICAL DRAWING:

