

Sewing Pattern — Jacket 6052

Recommendations on fabric: fabric of 150 cm width

You will also need: lining; fusible interfacing; 2 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part – 2 pieces
2. Side part – 2 pieces
3. Patch pocket – 2 pieces
4. Front band – 2 pieces
5. Front part – 2 pieces
6. Collar – 2 pieces
7. Upper sleeve – 2 pieces
8. Lower sleeve – 2 pieces

Lining:

1. Back part – 2 pieces
2. Side part – 2 pieces
7. Upper sleeve – 2 pieces
8. Lower sleeve – 2 pieces
9. Front part – 2 pieces

Interfacing: front parts, front bands, collar.

INSTRUCTIONS:

1. Apply the interfacing to wrong side of front parts, front bands, collar.
2. Stitch front darts. Stitch side part to front part.
3. Press pocket's upper edges into wrong side, fold them under and topstitch. Press pocket's open edges into wrong side and topstitch pockets according to marks.
4. Stitch back middle seam. Stitch back relief to the vent, press allowances backwards. Fold vent's left allowance into right side, stitch it along hem line, turn into wrong side and press it. Topstitch vent's left edge. Fold right back part's hem into right side, stitch along vent's allowance, fold into wrong side and press. Fold the vent sidewise and make diagonal stitch at vent's top to fix it. Press hem allowance into wrong side.
5. Stitch shoulder seams.
6. Stitch upper sleeve to lower sleeve to the mark. Stitch the zipper under slit's edges. Stitch sleeves into armholes. Press sleeves' hems into wrong side. Sew shoulder pads.
7. Stitch front bands to front parts' lining and stitch lining details in the same way as fabrics'.
8. Stitch inner collar into garment's neckline right side inside. Stitch outer collar into lining neckline. Lay the garment on the lining right sides together and stitch them together with one stitch: 3 cm of front bands' hems along front hem line, front edgings and the collar. Turn the garment right side out, press. Fix outer collar's lower edge on garment's back neckline.
9. Fold garment/sleeve hems under and sew to fabric garment's hems with blind stitches.
10. Make buttonholes into left front edging. Sew buttons on right one.

TECHNICAL DRAWING:

