

Sewing Pattern — Jacket 6049

Recommendations on fabric: gabardine of 150 cm width

You will also need: fusing; 4 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Center back part – 1 folded piece
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Collar – 1 piece
5. Center front part – 2 pieces
6. Front band – 2 pieces
7. Sleeve – 2 pieces

Fusing: collar.

INSTRUCTIONS:

1. Apply the fusing to wrong side of collar.
2. Sew back/front relieve seams. Press allowances apart.
3. Sew side/shoulder seams. Press allowances apart.
4. Fold collar detail along the center, right side out. Lay front bands on the garment, right sides together, insert the collar between them, then sew; at back neckline segment, slash outer collar and sew inner collar only. Turn front bands to wrong side, tack and press. Fold outer collar edge

under and topstitch on joining seam.

5. Sew sleeve seams. Sew sleeves into armholes. Press sleeve hems allowance to wrong side, fold them under and topstitch.

6. Press garment hem to wrong side, fold it under and topstitch.

7. Make buttonholes into left front part. Sew buttons on right front part.

TECHNICAL DRAWING:

