

Sewing Pattern — Anorak 6044

Recommendations on fabric: moreen/fabrics suitable for raincoats of 150 cm width

You will also need: elastic braid; separable zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Pocket – 4 pieces
2. Back part – 1 folded piece
3. Front part – 2 pieces
4. Hood – 2 pieces
5. Back sleeve – 2 pieces
6. Front sleeve – 2 pieces

INSTRUCTIONS:

1. Sew side seams leaving pocket entrance unstitched. Lay both sackings on garment wrong side on pocket entrance right sides together and pin them along pocket entrance. Sew sackings strictly along marked side seam lines, below pocket entrance, closely to the seam. Press sackings forward, tack to front part and topstitch along marking.
2. Sew sleeve upper seams. Press allowances forward and topstitch them.
3. Sew sleeve lower seams; do not stitch edges below bending line (to pull elastic braid in). Turn one-piece facing of sleeve lower edges to wrong side, fold them under and topstitch along coulisse marking. Pull elastic braids equal to wrist girth into coulisses. Topstitch braid ends.

4. Sew sleeves into open armholes; press allowances and topstitch.
5. Sew hood details. Press seam allowance to hood left part and topstitch. Turn hood allowance along face side to wrong side fold it under and topstitch. Sew the hood into neckline, leaving edge allowances behind ends of seam joining the hood. Press allowances of seam joining the hood downwards. Topstitch the garment along seam joining the hood.
6. Turn one-piece facing of garment hem to wrong side, fold it under and topstitch along coulisse marking. Pull elastic braids into coulisses, topstitch braid ends.
7. Press edging allowances to wrong side. Sew separable zipper under edgings with its teeth hidden; when sewing the zipper, fold zipper braid's upper ends under.

TECHNICAL DRAWING:

