

Sewing Pattern — Blouse 4292

Recommendations on fabric: natural/mixed blouse fabric

You will also need: 7 buttons, elastic tape of 1 cm wide (approx. length of the tape for one shoulder is mentioned on the flounce pattern) .

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem — 1.5 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Central front part – 2 details
4. Side front part – 2 details
5. Flounce — 2 details

Fusing:

1. Placket - 2 details

INSTRUCTIONS:

1. Apply fusing to the placket.
2. Sew princess edges on front and back parts. Serge seam allowances and press them towards center. Sew center edge of back part. Serge seam allowances and press them onto left side. Sew side seams. Serge seam allowances and press them towards back part.
3. Turn one-piece placket onto wrong side, turn seam allowance inside and topstitch at 0.2 cm off the edge.

4. Cut bias tape of 4 cm wide and as long as the armhole + 6 cm. Fold bias tape in half lengthwise wrong sides together and press. Fold the bias tape with the edge of the armhole on the right side, leaving tails, and overstretch. Turn bias tape onto wrong side, slash seams and topstitch along the fold onto main detail. Press the seam. Serge upper seam allowances of front and back parts.
5. Serge long edges of the flounce with rolled seam. Stitch loosely along marked line. Fold flounce along the stitch. Gather the flounce into a ruffle. Put flounce with its right side downwards onto wrong side of the blouse and stitch to top edge along the stitch that is gathering the ruffle. Fold flounce onto right side. Overstretch short sides of the flounce. Stitch elastic tape on shoulder section. Direct flounce downwards and put a fixing stitch at 1 cm off the top, stretching onto the elastic at the level of the ruffle.
6. Serge hem of garment. Fold seam allowance onto wrong side, press and topstitch.
7. Serge buttonholes on right side, sew buttons on left side.

TECHNICAL DRAWING:

