

Sewing Pattern — Pants 7155

Recommendations on fabric: napped knit fabric (jersey, stretchy velvet, fleece).

You will also need: fusible interfacing; elastic of 3 cm wide for waistband.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams – 1 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Front half – 2 pieces
2. Back half – 2 pieces
3. Front half cuff – 2 pieces
4. Back half cuff – 2 pieces
5. Waistband – 1 piece
6. Pocket sacking – 2 pieces
9. Side part – 2 pieces

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.



INSTRUCTIONS:

1. **POCKETS.** Apply interfacing to pocket entrance on front half. Stitch pocket sacking to front half and turn onto wrong side. Stitch pocket entrance. Put front half on side part according to matching line and sew sackings.
2. **ASSEMBLY.** Sew side seams. Sew front and back middle seams. Sew leg edges. Sew cuffs of front and back halves on leg seam and side seam up to slit mark. Fold cuff in half and overstretch the slit to control mark. Slash seam allowance. Stitch cuff to hem of trousers.
3. **WAISTBAND.** Sew waistband into ring, leaving a slit for elastic. Stitch waistband to trousers. Set elastic into the waistband and fasten it.
4. Press ready pants.

TECHNICAL DRAWING:

