

## Sewing Pattern — Sport jacket 7151

Recommendations on fabric: whipcord (polyester); knit fabric or fleece can be used as lining.

You will also need: Padding, fusible interfacing; 1 separable zipper (the length of zipper depends on the length of the garment front including stand collar); cord or piping; elastic of 3 cm wide for cuffs; elastic cord for hem; 2 fasteners or cord; 4 metal eyelets.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

**SEAM ALLOWANCE:** hem and hem of sleeves – 4.5 cm, along the edge of lining and button stand – 0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

#### Fabric:

1. Central front - 2 details
2. Central back - 1 detail
3. Side front – 2 details
4. Side back – 2 details
5. Central part of sleeve - 2 details
6. Side part of sleeve - 4 details
7. Collar- 2 details
8. Button stand - 2 details
9. Of-set welt – 2 details

Cut a bias tape of 3.5 cm width for piping. Length of bias tapes depends on the length of piping.

After making piping, seam allowance of 1 cm should be left, otherwise regulate the width of tapes at your pleasure.

#### Lining:

1. Front - 2 details
2. Back - 1 detail



3. Sleeve - 2 details
4. Pocket bag - 4 details

Padding:

Apply padding to the top collar, topstitching it along contour.

**INSTRUCTIONS:**

\*PIPING. Sew together tapes, press seams. Fold made tape in half, insert cord and put the stitch along contour of cord.

\*POCKETS IN SEAM WITH TOP-STITCHED OF-SET WELT. Apply fusible interfacing to off-set welt, fold in half and overstretch on sides. Turn out, press and stitch. Topstitch piping onto central front. Stitch pocket bag to side front. Put off-set welt onto central front (right sides together), then put pocket bag and topstitch with one seam on pocket opening. Turn out, press and stitch pocket opening. Sew pocket bags. Stitch side fronts to central fronts. Stitch. Stay-stitch on pocket opening, topstitch off-set welts onto front side. Edges of pocket bags should get into zipper connecting seam and reach hem line. \*MAIN ABRIC DETAILS ASSEMBLY. Stitch side parts to back, inserting piping. Stitch connecting seams. Stitch side parts of sleeves to central parts, inserting piping. Stitch sleeves to fronts and to back. Stitch sleeve connecting seam on rounded part. Sew side seams and seams of sleeves. Sew top collar into the neckline.

\*LINING. Topstitch button stand onto lining of front, having pressed beforehand inner edge of button stand. Sew lining of jacket. Sew lower collar into the neckline of lining.

\*ZIPPER. Put half of zipper to edge of button stand right sides together (zipper blade are directed from button stand). Overstretch edges of front bands and of collar with lining, sewing in zipper at the same time. Turn garment right side out.

\*Get eyelets along the edge of jacket. Press hem and hem of sleeves, turning under first at 1cm, then at 3.5 cm. Topstitch hem of the garment and hem of sleeves, leaving a slit in sleeve for elastic. Get elastic into hem of sleeves.

\*Stitch button stand and collar of jacket.

\*Press jacket when ready.

\*Get cord into hem of jacket.

**TECHNICAL DRAWING:**

