

Sewing Pattern — Trousers 7110

Recommendations on fabric: soft wool/knitwear

You will also need: elastic braid, decorative cord, tabs

Note: Waistband's elastic braid is of 3 cm width!

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams, 3 cm for hems

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Waistband – 1 piece
2. Back part – 2 pieces
3. Upper front part – 2 pieces
4. Lower front part – 2 pieces
5. Side pocket – 2 pieces
6. Side front part – 2 pieces
7. Flap – 4 pieces
8. Lower pocket – 2 pieces

Interfacing: flaps.

INSTRUCTIONS:

1. Apply the interfacing to wrong side of flaps.
2. Stitch upper front parts to lower front parts. Neaten the seam and press it downwards, topstitch from 0.2 cm from the seam.

3. Lay sacking on upper front part right sides together.
4. Neaten side seams, stitch them, press backwards.
5. Lay flaps right sides together, then overstitch. Cut corner allowances and turn right side out. Topstitch along flaps' contour at 0.5 cm from edges and neaten flaps' upper edges.
6. Neaten the pocket along contour and press it according to the pattern. Fold upper edge into wrong side and topstitch. Topstitch lower pocket on lower front part. Topstitch the flap, press it downwards and topstitch close to joining seam.
7. Stitch inseams and neaten them, press them backwards. Stitch front/middle edges. Make another stitch along crotch seam close to the stitch joining front/middle seam.
8. Neaten waistband's lower inner edge. Make holes for the cord into waistband. Press the waistband along the center right side out. Unfold the waistband and stitch it in ring.
9. Stitch waistband's outer part to trousers' upper edge. Topstitch waistband's lower neaten edge along waistband joining seam leaving a holes for elastic braid. Pull elastic braid in and stitch it in ring. Pull the cord in and set tabs.

TECHNICAL DRAWING:

