

Sewing Pattern — Sweater 7089

Recommendations on fabric: warmer

You will also need: braid

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams, 2.5 cm for sleeve hems, 2.5 cm for hood hem, 4 cm for upper sleeve edge

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Belt – 1 piece
3. Upper sleeve – 2 pieces
4. Lower sleeve – 2 pieces
5. Front part – 1 piece
6. Hood – 2 pieces
7. Center hood part – 1 piece

INSTRUCTIONS:

1. Stitch shoulder edges and neaten them, stitching braid. Press shoulder seams backwards.
2. Stitch lower sleeve to upper one and neaten the seam. Make a pleat into upper sleeve and topstitch it on lower sleeve with double stitch.
3. Stitch sleeves into armholes. Neaten joining seam and topstitch it on garment.
4. Lay hood details and stitch right sides together. Neaten joining seams and press them. Neaten them, fold under and topstitch hood edge.

5. Stitch the hood into neckline. Neaten joining seam (please note that hood edges must be one on another when stitching into neckline).
6. Stitch garment side seams and sleeves with one stitch, then neaten seams. Neaten sleeve hems, fold them into wrong side, press and topstitch.
7. Stitch belt side edge. Fold the belt along the center and stitch to the garment. Neaten joining seam and topstitch on the garment.

TECHNICAL DRAWING:

