

Sewing Pattern — Jacket 7034

Recommendations on fabric: proof cotton.

You will also need: cotton lining; warmer' 1 separating zip; 4 eyelets for coulisses; 4 eyelets for sleeve ventilation

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric 1:

1. Inner front part – 2 pieces
2. Middle front part – 2 pieces
3. Front cut-off armhole – 2 pieces
4. Armhole facing – 2 pieces
5. Front facing – 2 pieces
6. Back yoke – 1 piece
7. Lower back part – 1 piece
8. Back cut-off part – 2 pieces
9. Middle back part – 1 piece
10. Middle back facing – 2 pieces
11. Middle sleeve – 2 pieces
12. Collar – 2 pieces
13. Hood side – 2 pieces
14. Hood center – 1 piece
15. Patch pocket – 2 pieces
16. Front band – 2 pieces

Fabric 2:

1. Cut-off front edging – 2 pieces
2. Pocket facing – 2 pieces
3. Hood facing – 1 piece

4. Lower sleeve – 2 pieces
5. Upper sleeve – 2 pieces
6. Cuff – 1 piece

Lining:

1. Front part – 2 pieces
2. Back part – 1 piece
3. Sleeve – 2 pieces
4. Hood side – 2 pieces
5. Hood center – 1 piece
6. Patch pocket – 2 pieces
7. Upper sacking – 2 pieces
8. Lower sacking – 2 pieces

TECHNICAL DRAWING:

