

Sewing Pattern — Dress 7187

Recommendations on fabric: knit fabric of middle stretchiness of natural/mixed fibers;

You will also need: decorative elastic braid.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: on hem – 2cm, other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 folded detail
2. Front part – 1 folded detail
3. Sleeve – 2 details
4. Skirt – 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Stitch sleeves to front part, press and serge seam allowances. Stitch right sleeve to back part, press and serge seam allowances.
2. Press seam allowance of back and front parts' neckline and seam allowance of sleeve hem onto wrong side. Put decorative braid under neckline edge and sleeve hem and topstitch, stretching it. Length of the braid is 10% shorter than edge length.
3. Stitch left sleeve to back part, press and serge seam allowances. Sew right side edge and edges of sleeve with one seam. Press and serge seam allowances.

4. Stitch on top edge of the skirt loosely and tie up to the length of top part lower edge. Stitch skirt to top part, press and serge seam allowances. **Important:** to prevent cuts stretching, it is recommended to sew silicon band or elastic band into the seam.
5. Sew left side edge and edges of sleeve with one seam. Press and serge seam allowances.
6. Serge hem of the garment, press onto wrong side and topstitch.

TECHNICAL DRAWING:

