

Sewing Pattern — Overall 7135

Recommended fabric: medium-weight natural fabrics.

You will also need: fusible interfacing; 7 buttons; bias tape; elastic.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: all seams -1 cm; 1.5 cm on lower edge of placket.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Upper front – cut 2
2. Upper back – cut 1
3. Front pant – cut 2
4. Back pant – cut 2
5. Cuff – cut 2
6. Button placket - cut 2

INSTRUCTIONS:

1. Apply interfacing to plackets.
2. Sew center back pant seam. Serge and press seam toward left.
3. Gather upper edge of back pant, adjust fullness to length of upper back.
4. Sew back pant to upper back. Serge and press seam upwards.
5. Gather upper edge of each front pant, adjust fullness to length of upper front. Sew each front pant to each upper front. Serge and press seam upwards.
6. Pin fronts, right side together, and sew center front seam from notch down. Serge and press seam.

7. Fold placket in half lengthwise, wrong sides together, and press. Pin placket on front matching edges and sew at 1 cm from the edge of front along marked line. Snip into main garment at the end of closure aslant from the edge to ends of stitches, leaving 0.1 cm to the stitch. Turn plackets onto wrong side (top depends on baby's gender). Serge edges of plackets. Straighten the corner at the end of slit and fasten it with double stitch.
8. Sew and serge shoulder seams of front and back. Press seams toward back.
9. Finish the armhole and the neckline with bias tape.
10. Sew and serge side seams of front and back. Press seams toward back. Sew pant inseam with one seam. Press toward front and serge.
11. Sew cuff into ring, leaving an opening for elastic. Fold cuff in half lengthwise, wrong sides together.
12. Make a gathering stitch along lower edge of pant leg and gather fullness to match length of cuff. Stitch cuff to pant leg. Serge seam.
13. Mark and make buttonholes; sew buttons. Run elastic into cuff opening and sew ends of elastic together. Sew the opening closed.

TECHNICAL DRAWING:

