

## Sewing Pattern — Jumpers 7134

Recommendations on fabric: dense natural or mixed fabric (suiting or velvet)

You will also need: fusible interfacing; elastic, 2 buttons

If the pattern has a double line around it, the seam allowances are included. **Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm, hem of the garment – 3 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

### Fabric:

1. Back half – 2 details
2. Front half – 2 details
3. Central front half – 1 detail
4. Back facing – 1 detail
5. Front facing – 1 detail
6. Pocket lining – 1 detail
7. Strap – 2 details

Interfacing: seam allowance of pocket opening, front facing, back facing

### **INSTRUCTIONS:**

1. Apply interfacing to seam allowance of pocket opening, front facing and back facing.
2. Fold strap in half lengthwise, right sides together and overstretch on two straight edges. Trim in corners, turn strap right side out and press. Put decorative stitches at 0.2 – 0.5 cm off the edge.
3. Serge center edges of front and back halves.
3. Sew front center seam, leaving 2.0 – 3.0 cm to leg edges. Press seam apart. Lay pocket lining onto right side of front halves and overstretch pocket openings. Clip on curves. Turn lining to wrong side and press pocket opening. Put decorative stitch on pocket opening at 0.2 – 0.5 cm off the edge.

4. Put central part of front half under top part of front half, sew lining and central part of front half along the lower edge and serge seam. Fasten the pocket on top and side edge.
5. Sew and serge side and leg seams.
6. Sew center seam .
7. Sew and serge side seams of back and front facings. Place jumpers and facings right sides together and overstitch, inserting straps. Trim seam, turn facings to wrong side, press.
8. Topstitch elastic on back halves according to marks.
9. Serge hem of the jumpers, turn inside to wrong side and topstitch.
10. Fit jumpers on the child and align length of straps. Mark location of buttonholes and serge buttonholes. Sew buttons on front half.

**TECHNICAL DRAWING:**

