

## Sewing Pattern — Sweatshirt 7131

Recommendations on fabric: dense knit fabrics (french terry, fleece)

You will also need: fusible interfacing, zipper (length is shown on front pattern piece); decorative cord, 2 caps for cord, 2 snaps, elastic of 2,5 cm wide.

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; on armhole, sleeve curves, neckline, lower edge of hood - 0.7 cm; on outer edge of hood - 3 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

### **Main fabric:**

1. Front – 2 details
2. Back – 1 detail
3. Lower back – 1 detail
4. Lower front – 2 details
5. Sleeve – 2 details
6. Cuff – 2 details
7. Hood – 2 details
8. Central part of hood – 1 detail
9. Buttonstand – 2 details
10. Back neckline facing – 1 detail

Interfacing: buttonstand, back neckline facing



### **INSTRUCTIONS:**

1. Apply interfacing to buttonstand and back neckline facing. Apply interfacing to the place on hood where holes will be. Apply interfacing to seam allowance along buttonstand (for zipper).
2. Stitch side part of hood to central part and serge seams. Topstitch seam allowances onto central part. Mark holes location and serge holes on hood. Turn outer seam allowance of the hood onto wrong side, turn inside and topstitch onto the hood.
3. Place fronts right sides together and level edges, measuring the length of buttonstands. Stitch zipper to edge of buttonstand.
4. Sew shoulder seams. Serge seams and press toward back.
5. Sew shoulder seams of facing and buttonstand. Serge outer edge of buttonstands and facing. Put buttonstand onto right side of front right side downwards and overstitch on buttonstand line and on neckline, inserting hood between them. Overstitch from front side. Trim seam allowances on curves. Straighten buttonstands onto wrong side and press. Put decorative stitch along buttonstand at 0.5 cm from zipper.
6. Sew sleeve into open armhole. Sew and serge side seams and seams of sleeve at the same time.
7. Sew cuff into ring, leaving an opening for elastic. Fold cuff in half lengthwise, wrong sides together and stitch to sleeve. Serge seam.
8. Sew side seams of lower parts of back and of front. Press seams apart. Stitch upper edge of lower front to sweatshirt. Overstitch corners of lower details. Turn inner edge inside and topstitch into top edge connecting seam.
9. On lower details of front set snaps according to marks (depending on gender top of snap can be on left or right side). Set the cord into hood holes and put the cups on. Set the elastic into cuff and fasten it.

### **TECHNICAL DRAWING:**

