

Sewing Pattern — Sweatshirt 7130

Recommendations on fabric: dense knit fabrics (french terry, fleece)

You will also need: fusible interfacing, zipper (length is shown on front pattern piece); elastic of 2.5 cm wide.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; on armholes, sleeve curves, neckline and collar - 0.7 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Front – 2 details
2. Back – 1 detail
3. Lower back – 1 detail
4. Lower front – 1 detail
5. Sleeve – 2 details
6. Cuff – 2 details
7. Front waistband – 1 detail
8. Back waistband – 1 detail
9. Collar – 2 details

Interfacing: upper collar



INSTRUCTIONS:

1. Apply interfacing to upper collar and to edges of front band (for zipper).
2. Serge edges of front band. Measure the length of front bands and sew zipper so that zipper blade can be seen. Put decorative stitch along front band at 0.5 cm from the zipper.
3. Sew upper and lower fronts. Serge and press seam onto lower front.
4. Sew upper and lower backs. Serge and press seam onto lower back.
5. Sew and serge shoulder seams. Press seams onto back.
6. Fold details of collar right sides together and stitch on ends and outer edge. Trim corners, turn collar out and press. Sew upper collar into the neckline. Turn lower collar inside and topstitch into upper collar connecting seam.
7. Sew side seams. Serge seams and press them apart.
8. Sew side seams of front and back waistbands, leaving an opening for elastic. Fold waistband in half lengthwise, wrong sides together and stitch to lower edge of sweatshirt. Serge seam.
9. Sew and serge seams of sleeve. Sew seam of cuff, leaving an opening for elastic. Fold cuff in half lengthwise, wrong sides together and stitch to the sleeve. Serge seam.
10. Sew sleeve into armhole. Serge connecting seam from armhole side.
11. Set elastic into openings on waistband and cuffs and fasten it.

TECHNICAL DRAWING: