

Sewing Pattern — T-shirt 7117

Recommendations on fabric: sheer knitwear/fabric with elastic fiber

You will also need; trimming; chiffon/viscose/silk; piping

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams, 1.5 cm for garment/sleeve hems, 0 cm for front hem and neckline.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Front yoke – 1 piece
4. Upper front part – 1 piece
5. Middle front part – 1 piece
6. Front inset_1 – 1 piece
7. Front inset_2 – 1 piece
8. Front inset_3 – 1 piece
9. Sleeve – 2 pieces

INSTRUCTIONS:

1. Process lower edges of front yoke, upper/middle front parts and insets.
2. Mark place on inset_1, inset_2 and inset_3 on front part. Join insets together adjusting upper edges. Lay them on front part and topstitch according to marks on the pattern of front part.
3. Lay middle front part, upper front part and the yoke on front part consequently. Make fixing stitches along side seams. Armholes and the neckline at 0.5 cm from edges.

4. Neaten sleeve hems, fold them under and topstitch. Stitch sleeves into armholes according to marks. Neaten joining seams. Fold armholes' free edges and topstitch.
5. Overstitch edges of front/back necklines and sleeve upper edges with the piping.
6. Stitch garment's side edges and neaten them. Press side seams backwards.
7. Neaten garment's hem, fold it under and topstitch.

TECHNICAL DRAWING:

