

Sewing Pattern — Top 7108

Recommended fabric: natural or mixed fabric with stretch.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1 cm for all seams, 2 cm for arment/sleeve hems.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 1
2. Front– cut 1
3. Sleeve – cut 2
4. Sailor collar (back) – cut 2
5. Sailor collar (front) – cut 2

INSTRUCTIONS:

1. Sew side/shoulder seams. Serge and press seams toward back.
2. Sew sleeve seam, serge and press. Serge lower edge of sleeve, turn onto wrong side and topstitch.
3. Sew sleeves into armholes according to marks and adjust ease along cap. Serge seam.
4. Sew shoulder seams of outer/inner collars. Pin collars right sides together, and sew along outer edges. Trim corners, turn right side out, and press.
5. Sew sailor collar to neckline wrong side according to marks (the collar will be inside garment). Trim seam allowance to 0.4 cm width. Clip into curves. Fold sailor collar onto right side. Topstitch at 0.5 cm from neckline edge.
6. Serge lower edge of garment, turn onto wrong side, and topstitch.

TECHNICAL DRAWING:

