

Sewing Pattern — Cape 4144

Recommendations on fabric: well-draping, natural / mixed silk fabrics

You will also need: decorative thread

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams – 1 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Cape - cut 1

INSTRUCTIONS:

1. Serge center edges of back separately. Sew seam from edge up to marker. Press seam apart. Turn seam allowance along neckline inside and topstitch.
2. Serge lower edges, turn inside and topstitch.
3. Tassel: cut a piece of cardboard 10 cm high (length of ready tassel), width is 5 – 7 cm. Place a pencil at the top. Wind threads 20 – 30 turns. Take cardboard away, direct threads downwards from pencil. Hand-sew the tassel with the thread under the pencil. Remove the pencil. Run the thread through the loop and sew to the cape.

TECHNICAL DRAWING: