

Sewing Pattern — Trousers 7083

Recommendations on fabric: stretch cotton velvet/denim

You will also need: fusible interfacing; 1 zipper; 1 button; decorative fringe; elastic braid

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: 1 cm for all seams, 3 cm for hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Pocket – 2 pieces
2. Upper right front part – 1 piece
3. Middle right front part – 1 piece
4. Lower right front part – 1 piece
5. Upper left front part – 1 piece
6. Middle left front part – 1 piece
7. Lower left front part – 1 piece
8. Back part – 2 pieces
9. Belt loops – 1 piece
10. Waistband – 1 piece
11. Button catch – 1 piece

Interfacing: waistband, button catch

INSTRUCTIONS:

1. Apply interfacing to wrong side of waistband, button catch.
2. Stitch back darts. Press darts towards back part center.
3. Stitch front parts inserting decorative stitch between them. Neaten joining seams and topstitch them.
4. Press pocket upper edge into wrong side, fold it under and topstitch. Press pocket allowances into wrong side according to pattern. Topstitch the pocket on front part and topstitch.
5. Neaten front /middle edges of garment and garment lower edges. Stitch garment side edges. Neaten seams and press them. Stitch decorative braid to garment lower edge. Stitch leg inside seams and neaten them, press seams backwards. Neaten joining seam and press it. Stitch front edge and middle edge up to closure notch. Make another stitch along crotch seam close to seam joining front seam and middle seam.
6. Press closure one-piece facing into wrong side. Stitch the zipper under closure left allowance. Stitch zipper free braid to right one-piece facing. Fold button catch along the center wrong side out and overstitch along two sides. Turn button catch right side out and press it; then neaten button catch side. Stitch button catch to zipper closure left allowance. Topstitch slit right edge catching the facing.
7. Fold belt loop along the center wrong side out, adjust edges and overstitch at 0.5-0.7 cm from edges. Then turn right out, place the seam along fold line or making an edging of 0.1-0.2 –cm width into wrong side, and press it.
8. Press the waistband along the enter right side out and neaten lower inner edge. Cut belt loops according to size and topstitch them on waistband lower edge.
9. Stitch the waistband to garment upper edge. Cut elastic braid according to size. Topstitch elastic braid on waistband at side seams levels between upper belt loop and back one (on both sides). Overstitch waistband lower end, cut them at corners and turn right side out. Topstitch waistband lower neaten edge on joining seam and press ready waistband. Topstitch belt loops on waistband.
10. Make a buttonhole into right ends of waistband, and sew buttons on left end.

TECHNICAL DRAWING:

