

Sewing Pattern — Skirt 7066

Recommendations on fabric: silk, suiting

You will also need: fusible interfacing; 1 zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Back panel – 1 folded piece
2. Right front panel – 1 piece
3. Left front panel – 1 piece
4. Back yoke – 2 folded pieces
5. Front yoke – 2 folded pieces

Interfacing: lower yokes

INSTRUCTIONS:

1. Apply interfacing to wrong side of lower yokes.
2. Press front middle edge allowance to wrong side and topstitch. Lay right panel on left one coinciding middle lines and tack upper edges.
3. Sew lower yokes to panels' upper edges, press allowances towards yokes.

4. Sew right side seam. Sew left side seam between lower edge and closure mark, press allowances apart. Tack the zipper under slit edges and stitch at right side.
5. Sew side seams at lower yokes.
6. Overstitch garment upper edge with lower yokes, turn them to wrong side and press. Topstitch open edges of lower yokes on seam joining upper yokes at right side. Fold lower yoke side edges under and sew them to zipper braid.
7. Fold hem allowance to wrong side and topstitch.

TECHNICAL DRAWING:

