

Sewing Pattern — Dress 7060

Recommendations on fabric: gabardine

You will also need: lining; fusible interfacing; 1 long zipper; 2 short zippers.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Back yoke – 1 folded piece
2. Back lower part – 1 folded piece
3. Front lower part – 1 folded piece
4. Pocket – 2 pieces
5. Front yoke – 1 folded piece

lining:

6. Back part – 1 folded piece
7. Front part – 1 folded piece

INSTRUCTIONS:

1. Sew the zipper to back yoke. Sew yoke to back lower part.
2. Cut pocket entrance between mark lines, making diagonal notches to pocket marking corners. Press allowances apart. Lay the zipper under pocket entrance. Sew the zipper on right side at 0.1 cm from entrance of patch pocket. Press pocket allowances into wrong side, then topstitch.
3. Sew front yoke to front lower part.

4. Sew side seams.

5. Turn garment hem into wrong side and topstitch.

6. Sew back middle seam into lining to zipper mark. Sew side seams into lining. Apply lining and fabric details right sides together, then overstitch along edges of neckline and armholes, leaving slits of 1 cm near shoulder edges. Turn the garment right side out through shoulder seams. Sew shoulder seams in fabric details. Turn shoulder edges and lining closure's allowance into wrong side and sew by hand. Turn lining hem into wrong side and topstitch.

TECHNICAL DRAWING:

