

Sewing Pattern — Jacket 7056

Recommendations on fabric: patent fabric

You will also need: Velcro

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Back part – 1 folded piece
2. Front part – 2 pieces
3. Collar – 2 folded pieces
4. Sleeve – 2 pieces

INSTRUCTIONS:

1. Stitch shoulder/side seams.
2. Lay inner collar on outer one wrong sides out, and overstretch them along ends and collar fall. Turn the collar right side out and press it.
3. Fold one-piece front bands into right side and overstretch upper/lower corners. Cut allowances, fold front bands into wrong side, slash upper allowance neat the seam.
4. Stitch inner collar on the garment right sides together. Fold the collar upwards, press allowances towards the collar. Fold free edge of outer collar, fold it under and topstitch along the seam joining inner one.

5. Stitch sleeve seams. Stitch seams into armholes. Press sleeve hems into wrong side, fold them under and topstitch.
6. Press garment hem allowance into wrong side, fold it under and topstitch.
7. Topstitch Velcro pieces according to marks.

TECHNICAL DRAWING:

