

## Sewing Pattern — Trousers 7041

Recommendations on fabric: fabric with lycra of 150 cm width.

You will also need: fusing; 1 zipper; 1 button; 2 studs

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Flap – 4 pieces
2. Pocket – 2 pieces
3. Front part – 2 pieces
4. Back part – 2 pieces
5. Button catch – 1 piece
6. Waistband – 1 piece
7. Belt loop – 4 pieces

Fusing: waistband, button catch, inner flaps

### **INSTRUCTIONS:**

Apply the fusing to wrong side of waistband, button catch and inner flaps.

Press pocket allowances under, topstitch them on the front part according to marking.  
Sew side seams. Trim flaps along three sides, turn them right side out, press and topstitch along the edges. Sew flaps to garment parts according to marks, with its edge to pocket upper edge.  
Turn the flap so that it was on the pocket with its inner side.  
Press, then topstitch on 0,7 cm distance from joiningseam.

Fold front parts right sides together, sew front middle seam stopping 2 cm below inside leg seam.

Press zipper closure one-piece facing to wrong side. Sew the zipper under closure allowance left edge along the edge. Sew zipper free braid to right one-piece facing. Fold the button catch along the center wrong sides together, then neaten along long and short edges. Topstitch zipper closure one-piece facing onto garment left button catch. Topstitch right edge catching the facing.

Sew inside leg seams. Press seam allowances apart. Insert both parts one into another (right sides together). Sew middle seam upwards upper edge. Press middle seam allowances towards roundings.

Overstitch the belt loops along long and one of short edges. Sew the waistband to garment upper edge, right sides together, leave projecting piece on waistband left end for closure. When sewing, insert belt loop raw ends between waistband and the garment.

Press awistband joining seam allowance to the waistband. Fold the waistband along the center right side together and sew front ends. Turn the waistband right side out, topstitch it on the right side strictly along joining seam. Topstitch beltloops ready ends on the waistband.

Press garment hems under and topstitch.

Make a buttonhole into waistband right end, sew the button on the left one. Sew studs.

### **TECHNICAL DRAWING:**

