

Sewing Pattern — Blouse 7001

Recommendations on fabric: wool flannel.

You will also need: white cord of 1.8 m length; 6 buttons of 12 mm diameter; 6 bobs; 1 tassel

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 1 piece
2. Back part – 1 piece
3. Sleeve – 2 pieces
4. Collar – 2 pieces
5. Front coulisse – 1 piece
6. Front neckline facing – 1 piece
7. Back coulisse – 1 piece
8. Back neckline facing – 1 piece
9. Collar loop (rectangle of 3x5 cm) – 1 piece

INSTRUCTIONS:

1. Press front coulisse's short edges into wrong side, neaten them and stitch along edges.
2. Press coulisse's long edges into wrong side and stitch to front part according to marks.
3. Do the same for back coulisse.
4. Stitch side seams, neaten allowances and press apart as open.

5. Press blouse hem into wrong side, fold the edge under and stitch along edge.
6. Stitch collars right sides together along the perimeter excluding the segment of joining to back neckline, turn the detail right side out and press it.
7. Stitch neckline facing to allowances of front shoulder closure right sides together, fold shoulder closures' allowances into right side. Lay neckline facing on front part and stitch the neckline, turn right side out and press.
8. Stitch neckline facing to allowances of back shoulder closure right sides together, fold shoulder closures' allowances into right side and stitch between shoulder edge and collar stitching marks. Press allowances/facing into wrong side and tack along back neckline.
9. Press collar's open edges inside, insert back neckline between them and stitch all layers together; continue stitching along collar's contour.
10. Neaten with zig zags open edges of neckline facing/shoulder closures' allowances. Make fixing stitching along front shoulder allowance.
11. Tack allowance of front shoulder closure on back allowance along armhole.
12. Stitch sleeve seam and neaten allowances.
13. Stitch sleeves into armholes, neaten allowances, press toward armholes and make 5 mm decorative stitching.
14. Press sleeve hems into wrong side, press them under and stitch along edges.
15. Fold the loop along the center, stitch long edges, turn right side out and press the detail.
16. Stitch the loop into a ring and pull collar's ends into it.
17. Cut the cord into two equal pieces, pull into front/back coulisses, sew bobs on cords' ends.
18. Sew the tassel to back collar's end.
19. Make buttonholes into front shoulders.
20. Sew buttons on back shoulders.

TECHNICAL DRAWING:

