

Sewing Pattern — Sweatshirt 8005

Recommendations on fabric: knit fabric with napped wrong side (fleece, jersey)

You will also need: 1 separating zipper (zipper length depends on front length); cord for hood; 2 caps for cord, ready knit cuffs and waistband, twill ribbon of 1.5 - 2 cm wide

If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.



Seam allowances: on hood edge and edge of pocket opening – 2.5 cm, all other seams – 1cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

Fabric:

1. Front - cut 2
2. Back - cut 1
3. Sleeve - cut 2
4. Hood - cut 2
5. Center part of hood - cut 1
6. Pocket - cut 2
7. Waistband - cut 1
8. Cuff - cut 2

Advice:

To save elasticity on seam sections, sew details with narrow zig zag or special stretchy stitch or serge hem with overlock machine, and then stitch using double needle or with coverstitch machine. Sew other edges of the garment, that should stay stretchy, the same way. If there are no ready knit cuffs and waistband, you can make them from main fabric and set in elastic.

INSTRUCTIONS:

1. Turn and press seam allowance to inside and topstitch edge of pocket opening. Stitch pocket to front .
2. Stitch sleeves to front and back. Sew side seams and sleeve seams. Fold waistband in half lengthwise, right side out; stitch to garment right sides together, slightly stretching it.
3. Press and turn front edge. Sew zipper in. Stitch twilled ribbon along zipper connecting seam, covering zipper tape.
4. Sew parts of hood together. Work small round buttonholes on hood according to marks. Turn inside and topstitch seam allowance on front edge of hood. Sew hood into the neckline. Serge or finish neckline.
5. Sew cuffs into ring. Stitch cuffs to sleeves.
6. Thread cord into the hood.

TECHNICAL DRAWING:

