

## Sewing Pattern — Hat 7090

Recommendations on fabric: cotton, wool, dense silk or whipcord.

You will also need: lining, fusible interfacing.

Seam allowances: all seams - 1 cm.

### **Note on seam allowances:**

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.

- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### **Note on length of fabric:**

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



### **CUTTING:**

#### Main fabric:

1. Gusset – cut 6
2. Band – cut 1
3. Peak – cut 2
4. Button mould – cut 1

#### Lining:

1. Gusset – cut 6

#### Fusible interfacing:

1. Band – cut 1
2. Peak – cut 2

### **INSTRUCTIONS:**

1. Apply fusible interfacing to listed pieces.

2. Sew gussets together, placing them right side inwards. Topstitch along connecting seams at 0.2 cm from the seam. Sew center seam, aligning gussets exactly in the center. Topstitch along the seam.

3. Sew lining details the same way as main fabric details. Set lining into the head, matching seams on main fabric and lining. Turn inside lower edges of lining and main fabric and topstitch at 0.2 cm from the edge.
4. Place peak details right sides together and stitch on outer contour. Cut allowance close to the seam. Turn peak right side out, finish the seam, press. Topstitch peak with 0.5 cm parallel stitches. Level inner edge of the peak.
5. Sew band into ring and press apart the seam. Fold band in half lengthwise with its right side out, turn edges (separately) and baste.
6. Set the peak into the band, matching centers. Tack the peak and baste band edge. Topstitch the band with parallel stitches. Make first stitch at 0.2 cm from the edge, catching the peak. Gap between stitches is 0.5 cm.
7. Place band and head right sides together, baste, evenly distributing the ease and sew. Remove baste threads.
8. Envelope button with fabric and sew it in the center of the head.

**TECHNICAL DRAWING:**

