

## Sewing Pattern — Bag 3017

Recommendations on fabric: stiff natural/mixed fabric

You will also need: fusing, lining, decorative cord.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Upper part – 1 piece
2. Bottom – 1 piece

Lining:

1. Upper part – 1 piece
2. Bottom – 1 piece

Fusing: lining upper part, lining bottom.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of lining upper part, lining bottom.
2. Stitch upper part as a ring.
3. Stitch the lining as a ring leaving a hole for turning the bag right side out.
4. Cut a handle of 40 cm length and 4 cm width. Fold it along the center right side out, fold allowances into wrong side and make a stitch at 0.1 cm from the edge.
5. Set loops in bag's upper part.

6. Stitch upper part and the lining along upper edge inserting the handle as marked.
7. Fold upper part inside as marked. Make two round parallel stitches. Upper stitch goes along loop's upper edge, lower one goes along loop's lower edge.
8. Make a seam with loose upper stitches at 0.9 cm from lower edge. Gather the fabric. See gathering length on upper part's pattern.
9. Lining: make a seam with loose upper stitches at 0.9 cm from lower edge. Gather the lining. See gathering length on upper part's pattern.
10. Stitch the bottom to the bag. Stitch lining bottom to bag lining.
11. Turn the bag right side out. Stitch the hole.
12. Cut the cord into two equal parts. Set one of cords into the loop and, pull it through the coulisse and pull out from this loop. Do the same with another cord and another loop. Set tips on cord ends or tie them.

**TECHNICAL DRAWING:**

