

Sewing Pattern — Bag 3007

Recommendations on fabric: stiff natural/mixed fabric, faux/natural leather.

You will also need: fusing, lining, decorative handle, 1 snap

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams; 2 cm for partition pocket's upper edge

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Main part – 4 pieces
2. Side part – 1 piece
3. Facing – 1 piece
4. Facing's strengthener – 1 piece

Lining:

1. Main part – 2 pieces
2. Side part – 1 piece
3. Partition pocket – 2 pieces

Fusing: main part, side part, facing, facing's strengthener

INSTRUCTIONS:

1. Apply the fusing to wrong side of main/side parts, facing and facing's strengthener.
2. Stitch main part's middle edge. Fold allowances into left side, make 2 parallel stitches at 0.1 and 0.5 cm from the seam.

3. Stitch main parts to the side one. Fold allowances toward side part; make 2 parallel stitches at 0.1 and 0.5 cm from the seam.
4. Make a seam with loose stitches along bag's upper edge. Gather the fabric.
5. Cut lining flaps of 4 cm length and 2 cm width. Fold partition pocket's upper allowances into wrong side, then topstitch. Lay flaps half-and-half, lay them on the zipper's both sides. Lay partition pocket pieces on the zipper (lining does not hide zipper teeth), then topstitch.
6. Stitch lining right edges inserting partition pocket and leaving a hole to turn the bag right side out. Make a seam with loose stitches along lining's upper edge. Gather the lining.
7. Set a snap into facing's strengthener. Stitch side edges of facing's strengthener. Lay the facing on facing's strengthener right sides together and overstretch them along upper edge. Cut allowances, fold the facing into right side. Make decorative stitches at 0.1 cm and 0.5 cm from upper edge.
8. Stitch the bag to the facing. Stitch the lining to facing's strengthener.
9. Turn the bag right side out. Stitch the hole. Set eyelets into bag's facing. Пробить люверсы в обтачке сумки. Button the handle to eyelets.

TECHNICAL DRAWING:

