

Sewing Pattern — Bag 3004

Recommendations on fabric: faux/natural leather

You will also need: lining, 1 snap

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! Before sewing, print paper patterns and lay them out according to the linen width (from 90 to 150 cm) to find out how much material you need (do not forget about double and symmetric details).

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Leather:

- 1. Main part 1 piece
- 2. Fastener facing 1 piece
- 3. Side part 2 pieces
- 4. Facing 2 pieces

Lining:

- 1. Main part 1 piece
- 2. Side part 2 pieces



INSTRUCTIONS:

- 1. Lay fastener facing on main part right sides together and overstitch up to facing lower allowance.
- 2. Stitch side parts into the band; finish stitching at the same place as stitching of main part.
- 3. Stitch lining side parts and lining main part together slashing corner allowances.
- 4. Stitch facings' side edges in a ring.
- 5. Stitch facings on the lining right sides together leaving a hole to turn the bag right side out.
- 6. Lay facings wit lining on the bag right sides together, then overstitch them along upper edge. The first stitch goes along lower edge of fastener edge (Первая строчка по нижнему срезу обтачки застежки (bag covering folded into wrong side), the second stitch goes along bag's upper edge.
- 7. Turn the bag right side out. Stitch the hole. Set the snap.

TECHNICAL DRAWING:

