

## Sewing Pattern — Pullover 4319

Recommendations on fabric: thick, well draping knitted fabric of medium stretchiness

You will also need: 10 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: along hem of sleeve, necklines, fall shoulder edge and curve edge — 1.5 cm, all other seams - 0.8 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

#### Main fabric:

1. Back – cut 2
2. Outer part of front – cut 1
3. Inner part of front – cut 1
4. Sleeve — cut 2
5. Lower band — cut 1

#### Advice:

Knitted fabric details are sewn together with special elastic, narrow zig-zag stitch, or can be serged using an overlock machine. Seam allowance on hem is stitched with double needle to save stretchiness.

### **INSTRUCTIONS:**

1. Sew darts on inner part of front. Cut depths off with serger.
2. Sew center seams of back. Finish seams.
3. Finish the neckline of back. Turn seam allowances inside and topstitch. Finish, turn and topstitch neckline of fronts the same way.
4. Finish curved edge of outer front. Turn seam allowance inside and topstitch. Finish left shoulder edge of upper front. Turn seam allowance inside and topstitch.

5. Place upper part of front onto inner part and attach along right side and right shoulder seam and lower edge. Sew front pieces and back right side together and sew shoulder seams, turning back fall shoulder edge of outer front part. Finish seams and press towards back part. Sew sleeve into open armhole.
6. Sew side edge and edge of sleeve at the same time. Finish seams.
7. Sew lower detail into ring. Fold detail in half lengthwise and stitch to pullover. Finish seam.
8. Level button marks on fronts and sew buttons.
9. Serge hem of sleeve. Turn seam allowance onto wrong side, press and topstitch.

**TECHNICAL DRAWING:**

