

Sewing Pattern — Dress 4331

Recommendations on fabric: knit fabric of medium stretchiness in two colors.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on hem — 2 cm, along neckline — 1.5 cm, all other seams - 0.7 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Lower back — cut 2
2. Right front — cut 1
3. Left upper front — cut 1
4. Left lower front — cut 1

Contrasting fabric:

1. Upper back — cut 2
2. Upper front — cut 2
3. Cuff — cut 2

Advice:

Knitted fabric details are sewn together with special elastic, narrow zig-zag stitch, or can be serged using an overlock machine. Seam allowance on hem is stitched with double needle to save stretchiness.

INSTRUCTIONS:

1. Sew left parts of front. Serge seams and press them downwards. Stitch upper parts to fronts. Serge seams and press them downwards. Sew center edge of front. Serge seam.
2. Sew upper part of back to lower part. Serge seams and press them downwards. Sew center edge of back. Serge seam.
3. Sew shoulder and side edges. Serge seams.
4. Serge seam allowance neckline, turn inside and topstitch.
5. Sew cuff into ring. Fold cuff along center and stitch to hem of sleeve, stretching as necessary. Serge seam.
5. Serge hem of the dress, turn under and topstitch.

TECHNICAL DRAWING:

