

Sewing Pattern — Skirt 4335

Recommended fabric: natural or mixed suiting fabric.

You will also need: fusible interfacing; 1 blind zipper.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: all seams - 1 cm, outer edge of upper part — 2 cm, hem of the garment – 2 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Skirt back – cut 2
2. Back yoke – cut 4
3. Skirt front – cut 1
4. Front yoke — cut 2
5. Front panel — cut 1
6. Tie – cut 1

Interfacing:

1. Back yoke – cut 1
2. Front yoke – cut 1

INSTRUCTIONS:

1. Apply interfacing to outer yokes. Apply interfacing to upper edge of panel to avoid stretching. Serge upper, outer and lower edges of panel. Turn seam allowances inside and topstitch.
2. Stitch yokes to front and backs. Press seams open.
3. Serge center skirt back edges separately on each piece. Then sew center seam from zipper mark down to hem. Press apart seam allowances including opening for zipper. Sew in zipper.
4. Place panel with its right side upwards onto right side of skirt front and baste to side seam. Sew side seams of skirt front to skirt back. Serge seam allowances and press towards back.
5. Sew side seams of inner yokes. Press seam open. Serge lower edge of yokes. Sew side seams of outer yoke. Press seams open. Sew bottom edge of outer yoke to skirt, matching side seams. Place inner yoke with outer yoke, right sides together, and sew upper edge. Trim seam allowance. Understitch seam allowances onto inner yoke at 0.1 cm off the seam. Turn inner yoke onto wrong side, press. Topstitch inner yoke into outer yoke connecting seam. Tack yoke to zipper tape by hand.
6. Cut tie into two equal parts. Fold ties right sides together and sew on two long and one short side. Trim seam allowances in corners and turn right side out. Press ties. Topstitch ties according to marks on skirt and panel correspondingly.
7. Serge hem of the skirt, press onto wrong side topstitch.

TECHNICAL DRAWING:

