

Sewing Pattern — Jacket 4328

Recommended fabric: suiting or coat fabrics of natural or mixed fibers.

You will also need: fusible interfacing; lining; 4 buttons; shoulder pads; sleeve heads.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: all seams - 1 cm, on hem of the garment and hem of sleeve - 3.0 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 2
5. Buttonstand/facing (front band) – cut 2
6. Back neck facing – cut 1
7. Upper sleeve – cut 2
8. Lower sleeve – cut 2



Lining:

1. Center front – cut 2
2. Side front - cut 2
3. Center back– cut 2
4. Side back – cut 2
5. Upper sleeve – cut 2
6. Lower sleeve– cut 2

Attention! Front part and back part lining details are cut as using main pattern pieces except for the buttonstands/facing width and back neck facings accordingly.

Fusible Interfacing: center front, buttonstand/facing, back neck facing, garment hem and hem of sleeve.

INSTRUCTIONS:

1. Apply fusible interfacing.
2. On center back, sew and press darts towards center. On center front, sew darts and press toward hem. Sew side fronts to center fronts. Clip into curves and press toward center. Sew side backs to backs. Clip into curves and press toward center. Sew center back seam. Press seam open.
3. Sew front to back at side seams. Press seams open. Sew shoulder seams, trim in corner near neckline, press seam open. Sew center edge of collar, press seam open. Sew collar into the neckline of back, press seam open.
4. Sew back neck facing to buttonstand/facing. Clip into corners. Sew center edge of collar, press seam open. Sew collar to the neck facing, press seam open.
5. Place buttonstand/facing onto front, right sides together, pin and sew both buttonstand/facing and outer edges collars. Understitch. Sew lower corners of buttonstand. Trim seam allowances in corners. Turn buttonstand/facing to inside, straighten seams, press. Press hem of the garment.
6. Sew elbow sleeve seam, press seam open. Sew front sleeve seam, press seam open. Press hem of sleeve.
7. Sew a gathering stitch along sleeve cap for ease. Sew sleeves into armholes according to notches, easing around sleeve cap. Sew in shoulder pads and sleeve heads.
8. On lining pieces, sew seams and sew in sleeves, leaving an opening in front right seam of sleeve for turning. Press seams open.
9. Sew lining to inner buttonstand/facing edges and back neck facing. Tack seam allowances of collar connecting seam close to seams. Stitch lining to hem of jacket and to hem of sleeve. Turn jacket out through the opening in sleeve. Slipstitch opening closed.
10. Make buttonholes on both fronts according to marks. On left front, sew on a decorative button. On right front, on right side, sew a decorative button, from wrong side, sew an inner button.

TECHNICAL DRAWING:

