

Sewing Pattern — Skirt 4355

Recommendations on fabric: natural or mixed well-draping suiting fabrics

You will also need: fusible interfacing; zipper
If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm, lower edge of back - 3 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Back – cut 2
2. Side front – cut 1
3. Inner front – cut 1
4. Outer front – cut 1
5. Back facing – cut 2
6. Front facing - cut 1
7. Facing of outer front hem - cut 1
8. Facing of inner front hem - cut 1

Interfacing:

1. Back facing – cut 2
2. Front facing - cut 1
3. Facing of outer front hem - cut 1
4. Facing of inner front hem- cut 1

INSTRUCTIONS:

1. Apply interfacing to facings.
2. Sew darts on back, press darts toward center. Serge center edges of back separately, then sew center back seam from zipper mark down to lower edge. Press seam allowances apart, including the opening for zipper. Sew in zipper.
3. Make and baste pleats on outer front (pleats are directed downwards).
4. Serge inner edges of the hem facings of outer and inner fronts. Pin hem facings to fronts, right sides together, and sew. Clip into curves, understitch, and turn facings onto wrong side, straighten, press. Slipstitch facings to garment.
5. Pin outer front onto inner front, baste together, and treat as one piece. Sew front to side front. Serge and press seam toward side.
6. Serge lower edge of back. Sew side seams, serge and press toward back. Slipstitch hem of back.
7. Sew and press apart side seams of the waist facings. Serge lower edge. Place facing and skirt right sides together and sew. Clip into curves and understitch. Turn facings onto wrong side, press. Turn center edges of facing under, and tack to zipper tape. Tack facing to side seam allowances.

TECHNICAL DRAWING: