

Sewing Pattern — Skirt 4364

Recommendations on fabric: natural or mixed, light-weight suiting fabric

You will also need: fusible interfacing, invisible zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: all seams 1 – cm, lower edge of front and back - 3 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Back – cut 2
2. Front – cut 1
3. Front panel – cut 1
4. Back waistband; facing – cut 4
5. Front waistband; facing - cut 2

INSTRUCTIONS:

1. Apply interfacing to waistbands only.
2. Sew darts on back, press toward center. Sew back waistbands to back, serge and press seam upwards. Serge center back edges separately. Sew center back seam from mark down to lower edge. Press seam apart, including opening for zipper. Sew in zipper.
3. Make and fasten pleats on front panel (depths are directed downwards). Serge lower edge of panel, press onto wrong side, and topstitch. Pin panel on front and baste to top and side edges, then process as one detail (hem of panel is 3 cm shorter than front on right side edge).
4. Sew front waistband to front, serge and press seam upwards.
5. Sew side seams, serge and press seams toward back.
6. Sew and press apart side seams of facings. Serge lower edge. Pin facing and waistband right sides together and sew upper edge. Understitch, turn facing to wrong side, press. Turn center edges under, and slip-stitch to zipper tape. Topstitch facing into waistband connecting seam.
7. Serge lower edge of the skirt, press seam allowance onto wrong side, and slip-stitch.

TECHNICAL DRAWING:

