

Sewing Pattern — Blouse 4366

Recommended fabric: natural or mixed blouse fabric with lycra.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: on hem of the garment – 2 cm, all other seams – 1 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back - cut 2
2. Front - cut 1
3. Yoke_1 – cut 1
4. Yoke_2 – cut 1
5. Yoke facing_1 – cut 1
6. Yoke facing_2 – cut 1
7. Bow knot – cut 1

INSTRUCTIONS:

1. Sew darts on back, press toward center. Sew center back seam, serge and press seam toward left.
2. Sew bust darts, press toward hem.
3. Serge vertical edges of yoke facings_1. Pin facing and yoke_1 right sides together and sew top

and lower edges. Slash seam allowances near notch, turn the facing right side out. Serge vertical edges of yoke facings_2. Put facing and yoke_2 right sides together and sew top and lower edges. Slash seam allowances near notch, turn the facing right side out.

4. Pin yoke_1 on front, right sides together (shoulder edge of the yoke is directed downwards) and topstitch on marked line. Turn yoke upwards, baste to front on open edges. Then process as one detail. Pin yoke_2 on front, right sides together (shoulder edge of the yoke is directed downwards) and topstitch on marked line. Turn yoke upwards, baste to front on open edges. Then process as one detail. Sew together ends of yokes, press seam allowances apart and serge.

5. Fold bow knot in half lengthwise, right sides together and sew. Turn right side out, press, placing seam in the center. Lay bow knot on front, sew to neckline edge (under yokes).

6. Sew right shoulder seam, serge and press seam toward back. Cut or use ready-bias tape of 4 cm wide for finishing neckline. Fold bias tape in half lengthwise, wrong sides together and press. Pin bias tape on right side of neckline and stitch, turn bias tape onto wrong side and topstitch along the fold onto main fabric. Sew left shoulder seam, serge and press seam toward back.

7. Turn bow knot upwards, adjust the width, making pleats on yokes, and sew from wrong side to neckline.

8. Cut or use ready bias tape of 4 cm wide for finishing armhole. Fold bias tape in half lengthwise, wrong sides together, and press. Pin the bias tape to front side of armhole and sew, turn bias tape onto wrong side, and topstitch along the fold onto main fabric.

9. Sew side seams, serge, and press seam toward back.

10. Serge lower edge of garment, press onto wrong side, and topstitch.

11. Fold belt in half lengthwise, right sides together, and sew, leaving a small opening for turning out. Trim seam allowances in corners, turn belt right side out, and press. Sew the opening closed.

TECHNICAL DRAWING:

